

RECEIVED

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

JAN 13 1982

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Sacra SA Com
9. Well No. 1
10. Field and Pool, or Wildcat Und. Abo
12. County Chaves

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO deepen OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL OTHER-
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th St., Artesia, NM 88210
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>35</u> TOWNSHIP <u>6S</u> RANGE <u>25E</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3714.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 30' of 16" conductor pipe.
Spudded 12-1/4" hole at 3:00 PM 1-9-82. Ran 23 joints 8-5/8" 24# casing set at 925'.
1-Texas pattern notched guide shoe at 925'. Insert float at 885'. Cemented w/500
sacks Halco Lite with 2% CaCl₂. Tailed in w/200 sacks Class "C" with 2% CaCl. PD
5:00 PM 1-10-82. Circulated 50 sacks. WOC. Drilled out 2:00 PM 1-11-82. WOC 21
hours. Nipped and tested to 1000 psi, OK. Reduced hole to 7-7/8". Drilled plug
and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED William Goodlett TITLE Engineering Secretary DATE 1-13-82

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE JAN 19 1982

CONDITIONS OF APPROVAL, IF ANY: