

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

IL CONSERVATION DIV **RECEIVED**  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501  
**MAR 10 1982**  
**O. C. D.**  
**ARTESIA, OFFICE**

Form C-103  
Revised 10-1-78

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)OIL ☐ GAS ☒ OTHER ☐Name of Operator  
Yates Petroleum Corporation /Address of Operator  
207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM  
THE West LINE, SECTION 14 TOWNSHIP 9S RANGE 25E NMPM.15. Elevation (Show whether DF, RT, GR, etc.)  
3515' GR

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil &amp; Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name  
McCrea SF Com9. Well No.  
110. Field and Pool, or Wildcat  
Wildcat Abo12. County  
Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐PLUG AND ABANDON ☐  
CHANGE PLANS ☐OTHER ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 40' of 20" conductor pipe. Spudded a 14-3/4" hole at 8:00 AM 3-1-82. Ran 25 joints of 10-3/4" 40.5# K-55 casing set at 975'. 1-Texas Pattern notched guide shoe at 975'. Insert float at 935'. Cemented w/500 sacks Halliburton Lite, 2% CaCl<sub>2</sub>. Tailed in w/200 sacks Class "C" 2% CaCl. Compressive strength of cement - 800 psi in 12 hours. PD 1:45 AM 3-9-82. Bumped plug to 800 psi, released pressure and float held okay. WOC. Circulated 50 sx to the pit.  
Drilled out at 7:45 PM 3-9-82. WOC 18 hours. Nippled up and tested to 1000 psi, OK. Reduced hole to 9-7/8" to drill to 1500' then will reduce to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE Engineering Secretary

DATE 3-10-82

APPROVED BY

TITLE OIL AND GAS INSPECTOR

DATE

MAR 12 1982

CONDITIONS OF APPROVAL, IF ANY: