

NM OIL CONS. COMMISSION DEPARTMENT OF THE INTERIOR
Drawer DD GEOLOGICAL SURVEYArtesia, NM 88210
SUNDRY NOTICES AND REPORTS ON WELLS(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

C/SF

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

McKay Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2014, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FEL, Sec. 27, T.8S, R.22E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4035' G.L.

5. LEASE DESIGNATION AND SERIAL NO.

NM-22059

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

April

9. WELL NO.

#2

10. FIELD AND WELLS OR WILDCAT

Undesignated Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T.8S, R.22E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-8-82 TD 1500', Ran 33 jts of 8-5/8" 24# J-55 ST&C csg (1432.40')
Cmt'd w/200 sx Thixolite, 625 sx Pacesetter Lite & 300 sx
Cl "C" neat cmt. Bumped plug @ 4:45 PM on 1/8/82 w/750 psi,
held okay.

Ran Temp Survey, TOC 400'.

SET SIX PLUGS WITH A TOTAL OF 400SX TO CIRCULATE

1-17-82 TD 3306', Ran 76 jts of 4 1/2" 10.5# J-55 ST&C csg (3306.24').
Cmt'd w/350 sx 50/50 POZ "C". Bumped plug @ 12:30 PM on
1-17-82 w/1250 psi, held okay.

RIG RELEASED @ 12:30 PM on 1-17-82.

RECEIVED
JAN 25 1982OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Production Analyst

DATE

1-21-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side