

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒  
well well other
- 
2. NAME OF OPERATOR  
MESA PETROLEUM CO.,
- 
3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  
below.)  
AT SURFACE: 660' FSL & 760' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
- 
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- |                      |                          |
|----------------------|--------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/> |
| FRACTURE TREAT       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE    | <input type="checkbox"/> |
| CHANGE ZONES         | <input type="checkbox"/> |
| ABANDON*             | <input type="checkbox"/> |

ABANDON\* ☐  
(other) 8 5/8" Casing & Cement

SUBSEQUENT REPORT OF:

- |  |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole to 1815' and ran 47 jts, 8 5/8", 24#, K-55 casing set at 1815'. Cemented with 750 sx HLW + 1# flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 12 Noon, 12-15-81. Cement did not circulate. Ran temp survey - TOC at 1220'. Set two plugs with a total of 600 sx Thixset + 4% CaCl to raise TOC to 520'. Tested BOPs and casing to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled ahead on 12-16-81.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

REGULATORY COORDINATOR

OR DATE 12-18-81

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD <sup>(Th)</sup>  
PETER W. CHESTER  
 APPROVAL IF ANY:

TITLE

DATE \_\_\_\_\_

DEC 23 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side