

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

*C/SF*  
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL / 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud, 13 3/8" csg # cement

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE

NM-40030

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
LODEWICK FEDERAL

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 17 T5S R25E

12. COUNTY OR PARISH 13. STATE

CHAVES

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3857.2' GR

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 17 1/2" hole on 12-29-81. Drilled to 892' and ran 21 jts of 13 3/8", 48#, H40 casing set at 892'. Cemented with 700 sx HLW + 1% Flocele + 4% CaCl, 400 sx Thixset + 4% CaCl, and tailed-in with 300 sx "C" + 2% CaCl. PD at 12:00 midnight. Cement did not circulate. Ran temp. survey - TOC at 400'. Set nine plugs with a total of 1200 sx Thixset + 4% CaCl and 1300 gal Flo-chek to circulate cement. WOC 8 hours, blew hole dry and waited one hour - no fluid. Reduced hole to 12 1/4" and drilled ahead on 1-2-82. WOC total of 38 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*R. A. Chapman*

TITLE

REGULATORY COORDINATOR

DATE

1-6-82

ACCEPTED FOR RECORD  
(This space for Federal or State office use)  
ROGER A. CHAPMAN

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JAN 11 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side