

RECEIVED
JAN 15 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

UNITED STATES
DEPARTMENT OF THE INTERIOR
C/SF GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Estoril Producing Corporation

3. ADDRESS OF OPERATOR

79701

11th Floor, Vaughn Bldg. Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1650' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: "

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Casing & Cement

SUBSEQUENT REPORT OF:

RECEIVED
JAN 15 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-6-82 TD 5000'

Ran 93 joints (3649'), 4½" 10.5#, J-55 ST&C casing and set at 3649'.

Cemented with 700 sx of Pacesetter 'C', 1# Perma Check/sk, ½# Cello Seal/sk, 2% KCL, followed by 200 sx 50-50 Pozmix, .6% CF-9, .3% TF-4, 3% KCL.

Full circulation throughout job. W.O.C. 12 hours. Pressure tested casing 1000 psi for 30 minutes.

Subsurface Safety Valve: Manu. and Type

ROGER A. CHAPMAN

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

JAN 15 1981

TITLE Agent

DATE

1/14/81

(This space for Federal or State office use)

U.S. GEOLOGICAL SURVEY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE