

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR  
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
660 FNL & 1980 FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


- | REQUEST FOR APPROVAL TO:                      | SUBSEQUENT REPORT OF:               |
|---|-------------------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input checked="" type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/>            |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/>            |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/>            |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/>            |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/>            |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/>            |
| ABANDON* <input type="checkbox"/>             | <input type="checkbox"/>            |
| (other) <input type="checkbox"/>              | <input type="checkbox"/>            |

5. LEASE  
NM 28162
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Thorpe MI Federal
9. WELL NO.  
6
10. FIELD OR WILDCAT NAME  
Und. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit C, Sec. 14-7S-25E
12. COUNTY OR PARISH  
Chaves
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3746.9' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 23 joints of 10-3/4" 40.5# casing set at 900'. 1-Texas Pattern guide shoe at 900'. Insert float at 861'. Cemented w/500 sacks Halliburton Lite 2% CaCl<sub>2</sub>. Tailed in w/200 sacks Class "C" 2% CaCl<sub>2</sub>. PD 12:45 PM 12-24-81. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. Drilled out at 1:30 PM 12-26-81. WOC 48 hours and 45 minutes. Nipped up and tested to 1000 psi, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

TITLE Engineering Secty DATE 12-28-81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

JAN 5 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO