

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other \_\_\_\_\_
2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
660' FNL & 660' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

X							
---	--	--	--	--	--	--	--

DECEIVE  
JAN 25 1982 (NOTE: Her  
ch)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE NM 19416

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME  
Langley RJ Federal

FEB 24 1982

9. WELL NO. 1

O. C. D.

10. FIELD OR WILDCAT NAME

ARTESIA, OFFICE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit D, Sec. 9-T6S-R25E

12. COUNTY OR PARISH	13. STATE
Chaves	NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4037.8' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 12-1/4" hole at 1:30 AM 1-18-82. Ran 25 joints of 8-5/8" 24# J-55 casing set at 960'. 1-Texas Pattern guide shoe set at 960'. Insert float set at 926'. Cemented w/500 sacks Pacesetter Lite "C" with 2% CaCl<sub>2</sub>. Tailed in w/300 sacks Pacesetter Lite "C" with 2% CaCl<sub>2</sub>. PD 8:00 PM 1-19-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 40 sacks to pit. Drilled out 2:00 PM 1-20-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: ~~Manu~~ and ~~Record~~

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

1  
TITLE Engineering Secty DATE 1-21-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

DATE \_\_\_\_\_

U.S. GEOLOGICAL SURVEY  
APPROVAL, IF ANY  
ROSWELL, NEW MEXICO