

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Dry

2. NAME OF OPERATOR
Southland Royalty Company ✓

3. ADDRESS OF OPERATOR
1100 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
660' FNL & 1980' FEL, Sec. 35, T-10-S, R-29-E

RECEIVED BY
AUG 01 1985
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
NM-16804

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Sand Ranch "35"

9. WELL NO.
1

10. FIELD AND POOL, OR WIELDCAT
Undesignated (Cisco)

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
Sec. 35, T-10-S, R-29-E

12. COUNTY OR PARISH
Chaves

13. STATE
N.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3965.6' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. MIRU PU. POH w/tbg & pkr.
2. Set cmt retainer @ 8041'. Squeezed perfs 8118-28' w/50 sx C1 "H" to 7000#. (42 sx in perfs & 8 sx in csg). TOC @ 8018'. Pull tbg to 8000'. Displace hole w/10# mud. POH.
3. Removed tbg head. Weld onto 4½" csg. Pull on csg.
4. Shot 4½" csg @ 6734'. LD 154 jts of 4½" csg. Ran tbg to 6809'. Spot 50 sx cmt from 6809-6659'. Pull tbg to 4850'.
5. Tagged cmt plug @ 6620'. Pull tbg to 3968'. Spot 35 sx from 3968-3846'. Pull tbg to 2697'. Spot 75 sx cmt. Pull tbg to 1800'. Waited 3 hrs. Tag cmt plug @ 2420'. Pull tbg to 405'. Spot 75 sx cmt from 405-175'. 20 sx cmt plug @ surface.
6. Cut off casinghead. Weld plate on csg. Install dry hole marker. RD plugging unit. Plug and abandon 6-16-82.

Post ID-2
7-9-82
P+H

RECEIVED
JUN 18 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Frey N. Rank

TITLE District Operations Engineer

DATE 6-18-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
PETER W. CHESTER

JUL 30 1985

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA