

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
NW OIL COMS. CO. LOCATION
SUBMIT IN (Other instructions on re-verse side)
Artesia, NM 88210Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 17576	
2. NAME OF OPERATOR Sanders Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 11000-D Spain N.E., Albuquerque, NM 87111		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2050' FNL & 1960' FEL Section 6		8. FARM OR LEASE NAME Isler Federal	
14. PERMIT NO.		9. WELL NO. #3	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3885' GL		10. FIELD AND POOL, OR WILDCAT Undesignated Abo	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 6, T7S, R27E	
		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing & Cement

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 134 jts. 4-1/2" 10.5# K-55 Seamless API Casing. Set at 4986', Top of Float Collar 4947'. Cemented with 180 sx. 65/35 poz with 6% gel, 3% CaCl, 8 lbs. Gilsonite, 1/4 lb. celloflake, 5 lbs. salt, followed by 130 sx. self-stress "C" with 2% CaCl, 1% FLA, 1/4 lb. celloflake. Plug down at 2:44 am, 02-14-82. Top of Cement by Temperature Survey 3790'.

RECEIVED
FEB 22 1982OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE 02-17-82

(This space for Federal or State use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side