

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
Stevens Operating Corporation /

3. ADDRESS OF OPERATOR  
P. O. Box 2408, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1980 FWL, 660 FWL, Sec 13,  
AT SURFACE: T7S, R25E  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Run Casing and Perforate			

5. LEASE  
NM 43524

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
Edmondson Federal

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
Undesignated Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 13, T7S, R25E

12. COUNTY OR PARISH  
Chaves

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3706.5 GR

RECEIVED

1982

O.C.D.

ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/28/82 Ran 103 joints 4½" 10.5# casing. Set and cement at 4149' w/250 sks Self Stress w/2% CaCl<sub>2</sub>. Plug down at 12:00 a.m., pressured up 1000#, plug held.

3/4/82 Perforated at 3859, 61, 61.5, 62.5, 63, 63.5, 67.5, 68, 68.5, 70.5, 71, 71.5, 75.5, 76, 80.5, 81, 81.5, 87.5, 88, 88.5, 3930.5, 31, 31.5, 39.5, 40, 40.5, 44.5, 46.5, 47, 47.5, 50.5, 51, 51.5, 56, 56.5, 58, 58.5, 62, 62.5, 63.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Prod. Coordinator DATE 3/19/82

APPROVED BY \_\_\_\_\_ (This space for Federal or State office use)  
CONDITIONS FOR APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
MAR 25 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO  
MAR 22 1982