

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980/N 1980/W, Sec. 14-T6S-R25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Perforate ☐

5. LEASE

NM 10263

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Thomas LN Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Pecos Slope Abo Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit F. Sec. 14-T6S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3860.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4282'. WIH and perforated 3723-3890' w/14 .40" holes as follows: 3723' (1 hole), 3724-26' (4 holes), 3808-3812' (8 holes) and 3890' (1 hole). Acidized perforations 3890' w/500 gallons 7½% Morroflo acid. Acidized perforations 3808-12' w/1500 gallons 7½% Morroflo acid and acidized perforations 3723-26' w/500 gallons 7½% Morroflo acid. Sand frac'd perforations 3723-3890' (via tubing & casing) with 40000 gallons gelled KCL wtr, 2 loads CO2 and 80000# 20/40 sand. Well stabilized at 275 psi on 3/4" choke = 4173 mcfpd.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Leanna Goodrich TITLE Engineering Secty DATE 4-5-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: