

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

HUSKY OIL COMPANY✓

3. ADDRESS OF OPERATOR

600 S. Cherry St., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 670' FNL & 660' FWL, NW $\frac{1}{4}$  NW $\frac{1}{4}$

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spudded and Spotted Cement

SUBSEQUENT REPORT OF:

RECEIVED  
JAN - 8 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well @ 3:00 p.m. 12/28/81.

12/30--Tried to run 4 jts 13-3/8" surface csg. Stuck & stopped @ 125'. Pulled csg. Reamed to 540' KB.

12/31--Spotted 50 sx Thixolite w/1.5 pps Permacheck + 1/2 pps Celloseal.

1/1 --Reamed to bottom & tagged @ 510'. No circulation.

Spotted 75 sx Thixolite. Reamed to bottom & tagged @ 440'. No circulation.

Spotted 150 sx Pacesetter Light + 1 pps Permacheck + 1/4 pps Celloseal + 2% CaCl<sub>2</sub>.

1/2 --Reamed to 240'. Tagged TOC.

Spotted 200 sx pacesetter Light. No circulation. (Ground started sinking under rig.)

1/3 --Reamed to 210'. Tagged cmt. Spotted 150 sx Pacesetter Light.

Reamed to 190'. Tagged cmt. Spotted 150 sx Class "C" + 2% CaCl<sub>2</sub> + 1% cedar fibers.

Reamed to 60'. Tagged cmt. Spotted 150 sx Class "C" + 2% CaCl<sub>2</sub>.

Reamed to 60'. Tagged cmt. Spotted 50 sx Pacesetter Light.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Roger A. Chapman ACCEPTED FOR RECORD TITLE Engr. Assistant DATE January 5, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: JAN 11 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

JAN 12 1982