UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS UP not use in form of the dense of properties of difference of difference of the dense of properties of difference of differenc	SF
UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS CONTROL OF THE SAND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS CONTROL OF THE SAND REPORTS ON WELLS CONTROL OF THE SAND REPORTS ON WELLS CONTROL OF THE SAND REPORTS ON WELLS CONTROL OF PERATOR SET OF OPERATOR ANTE OF OPERATO	roved. Areau No. 42-R1424
GEOLOGICAL SURVEY         GEOLOGICAL SURVEY         SUNDRY NOTICES AND REPORTS ON WELLS         Colspan="2">Colspan="2"         I Colspan="2"       Colspan="2"       Colspan="2"       Colspan="2"       Colspan="2" <t< td=""><td></td></t<>	
SUNDRY NOTICES AND REPORTS ON WELLS.         SUNDRY NOTICES AND REPORTS ON WELLS.         Con du sub liver mile proposite a different disease or public State of different different disease or public State of different	
SUNDART WOILDES AND REFORMED AND REPORTS AND REPORT AND REPORTS AND REP	TRIBE NAME
I. off DR gas	;
weil L2       weil L1       coher       JUL 1       100.       11       00.       11       00.       <	
2       NAME OF OPERATOR Berge Exploration, Inc.       O: C. D. ADDRESS OF OPERATOR 7100 N. Broadway, 2-L, Denver, CO 80221       No. 11-03402514         3. ADDRESS OF OPERATOR 7100 N. Broadway, 2-L, Denver, CO 80221       I. FIELD OW WILCAT MANU Less I is Spin S. Sec. 26, T.7S., I Sec. 20, Sec. 26, T.7S., I Sec. 20, Sec. 26, T.7S., I Sec. 20, Sec. 26, T.7S., I Sec. 26, Sec. 26, T.7S., I Sec. 26, Sec.	
Delige CAPTOR CONTRACTOR       ARTESIA, OFFICE         ADDRESCAP CONTRACTOR       ARTESIA, OFFICE         7100 N. Broadway, 2-L, Denver, CO 80221       IL sec. T, R, M. OR BLK, AREA         AL DECATION OF WELL (REPORT LOCATION CLEARLY. See space 17       Sec. 26, T. 75., 1         AT TOP PROD. INTERVAL: (as above)       IL API NO.         AT TOP PROD. INTERVAL: (as above)       IL API NO.         IS. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA       IL API NO.         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TEST WATER SHUT-OFF       Image on Form 9-330.         PULL OR ALTER CASING       Image on Form 9-330.         MULTIPLE COMPLETE       Image on Form 9-330.         Charge stimated date of starting any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.)*         Drilled to 205'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu 11Y.         US. GEOLOSM       Subsurface Safety Valve: Manu, and Type         Subsurface Safety Valve: Manu, and Type       Set @         Is. I hereby certify that the foregoing is true and correct       Signed         Gring space for Federal or State office use)       Onte         APPROVED BY       TITE       OPATE	
A DOROS N. Broadway, 2-L, Denver, CO 80221       11. SEC. T. R. M. OR BLK.         A LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)       11. SEC. T. R. M. OR BLK.         A TOP PROD. INTERVAL: (as above)       11. SEC. T. R. M. OR BLK.         AT TOTA DEPTH: (as above)       12. COUNTY OR PARISH: 13         Chaves       1         AT TOTA DEPTH: (as above)       14. API NO.         15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.       14. API NO.         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TRACTURE TREAT       Image: Charles of the count o	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 2318.4 FEL x 1661 FSL AT TOP PROD. INTERVAL: (as above) AT TOTAL DEPTH: (as above)       AREC. 26, T.75., 1 32. COUNTY OR PARISH 13 Chaves         18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA       Is ELEVATIONS (SHOW DF 3818.7 GL         REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PRACTURE TREAT       Indicate PROPOSED OF REPAR WELL PULL OR ALTER CASING       Interval: Indicate getimated date of stating any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.) <sup>2</sup> 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give including estimated date of stating any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.) <sup>2</sup> Drilled to 296'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu LIY.         JUN 2.1 OIL & U.S. GEDIOGN ROSWELL, NE Subsurface Safety Valve: Manu. and Type IS I hereby certify that the foregening is true and correct SIGNED	
AT SUFFACE: 2318.4 FEL x 1661 FSL AT TOP PROD. INTERVAL: (as above) IS. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF REPARTURE TREAT SMOOT OR ACIDIZE HERATINE COMPLETE CHANGE ZONES ABANDON- TO ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give including estimated date of stating any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10. 4 feet due east. Plugged hole w/85 sax. cement. Change well nu LIY. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type TITLE State office use TITLE State office use TITLE	
AT TOP PROD. INTERVAL: (AS above) AT TOTAL DEPTH: (AS above) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF 3818.7 GL 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give including estimated date of starting any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu 117. DECIEST Subsurface Safety Valve: Manu. and Type Set @ 18. I hereby cértify that the foregeing is true and correct SIGNED	
	N.M.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:     3818.7 GL     3818.7 GL     3818.7 GL     3818.7 GL     100 0 CF	· • •
TEST WATER SHUT-OFF       Image: constraint of the space for Federal or State of free state of multiple constraints of multiple constraints of the space for Federal or State of free state and correct stigned by that the foregoing is true and correct         Subsurface Safety Valve: Manu. and Type       Image: constraints of the space for Federal or State of the state of free state of the state of free state of the state state state of the state stat	KDB, AND WD)
FRACTURE TREAT       Image: constraint of multiple computer coulds of many proposed work. If well is directionally drilled, give subsurface safety Valve: Manu. and Type       Image: could could be could	······································
REPAIR WELL       (NOTE: Report results of multiple change on Form 9-330.)         PULL OR ALTER CASING       (NOTE: Report results of multiple change on Form 9-330.)         MULTIPLE COMPLETE       (Atternet the state of the state o	
PULL OR ALTER CASING	
CHANGE ZONES ABANDON* (other) <u>Change-wellerininber</u>	
(other)       CBange wetheritimber         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give including estimated date of starting any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.)*         Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu 11Y.         Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu 11Y.         Olt & customer in the state of th	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurf measured and true vertical depths for all markers and zones pertinent to this work.)*         Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu lify.         Drilled to 206'. Could not get sfc csg. down. Abandoned hole and 10.4 feet due east. Plugged hole w/85 sax. cement. Change well nu lify.         Dif & could not get sfc csg. down. Abandoned hole and 0.4 feet due east. Plugged hole w/85 sax. cement. Change well nu lify.         Subsurface Safety Valve: Manu. and Type	
OIL & C U.S. GEOLOGIU ROSWELL, NE Subsurface Safety Valve: Manu. and Type	moved location
OIL & C U.S. GEOLOGIU ROSWELL, NE Subsurface Safety Valve: Manu. and Type	2005 CD
OIL & C U.S. GEOLOGIU ROSWELL, NE Subsurface Safety Valve: Manu. and Type	
OIL & C U.S. GEOLOGIU ROSWELL, NE Subsurface Safety Valve: Manu. and Type	
U.S. GEOLOGIN ROSWELL, NE Subsurface Safety Valve: Manu. and TypeSet @ 18. I hereby certify that the foregoing is true and correct SIGNED	1982 川 人
Subsurface Safety Valve: Manu, and Type	CAL SURVEY
18. I hereby certify that the foregoing is true and correct         SIGNED       JUNCA         TITLE       Vice President         OATE         (This space for Federal or State office use)         APPROVED BY       DATE	Ft.
SIGNED MUR (P.Survey TITLE Vice President DATE	
APPROVED BY DATE TITLE	
	OVED
1	
•See Instructions on Reverse Side FOR AA	3,0 1982 X . Gillham