STATE OF NEW MEXICO					
ENERGY AND MINERALS DEPARTMENT					
•• •* corice +cccives 12	L CONSERVA	TION DIVIS	JON		
DISTRIBUTION	P. O. BOX		RECEIVED		Form C-103
BANTA FE /		•			Revised 10-1-78
FILE /	SANTA FE, NEW	MEXICO 8750	•		
U.S.G.S.		Δρι	R 1 2 1982	Sa. Indicate Type o	of Leise
LAND OFFICE				State X	Fon
OPERATOR / AMEN	DED_ <u>REPORT</u> *		). C. D.	5. State Oti & Gas	Lease No.
				LG-249	
SUNDRY NOTICES	AND REPORTS ON	WELLS ARI	SIA, OFFICE	THIMM.	TITITITI I
IDD NOT USE THIS FORM FOR PROPOSALS TO ORIL USE "APPLICATION FOR PERMIT	- TO DELPEN OR PLUG NA	CA TO A DIFFERENT I	ISERVOIR.		
				ムネーストス スタイス スプラ 7, Unit Agreement	
OIL GAB THER-					
Name of Operator				8. Farm or Lease Hame	
Yates Petroleum Corporation /				Collins SW State	
Address of Operator				9. Well No.	
207 South 4th St., Artesia, NM 88210				1	
Location of Well				10. Flold and Pool, or Wildcat	
UNIT LETTER 660 FEET FROM THE NOTTH LINE AND 660 FEET FROM				Und. Pecos Slope Abo	
UNIT LETTER	FROM THE NULLI	LINE ANDOOL	FEET FROM	mmm	minn
Most 25	4.0	0.4		MMMM	
THE West LINE, SECTION 25 TOWNSHIP 48 RANGE 24E NMPM.				/////////	/////////
, TTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT				71111111	http://http://
				12. County	
	<u> </u>			<u>Chaves</u>	ΔΠΠΠΠ
Check Appropriate	Box To Indicate Na	ature of Notice	, Report or Othe	er Data	
NOTICE OF INTENTION T			SUBSEQUENT		
ERF DAM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERIN	
TMPORARILY ABANDON		COMMENCE DRILLING	OPNS.	PLUG AN	
ULL DE ALTER CABING	CHANGE PLANS	CASING TEST AND CE	, <u>,</u> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
		OTHER			
		JINER		······	<b>I</b>
018C8	[]				
Describe Proposed or Completed Operations (Clear	ly state all pertinent deta	ils, and give pertine	nt dates, including e	stimated date of st	arting any proposed

work) SEE RULE 1103.

Spudded a 12-1/4" hole at 9:00 AM 4-1-82. Set 30' of 20" conductor pipe. Ran 23 joints of 8-5/8" K-55 ST&C casing set at 928'. 1-Texas Pattern notched guide shoe at 928'. Insert float at 888'. Cemented w/500 sacks Howco Lite and 2% CaCl<sub>2</sub>. \*Tailed in w/200 sacks Class "C" 2% CaCl<sub>2</sub>. PD 2:15 PM 4-2-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 8:15 AM 4-2-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TITLE

IONS OF APPROVAL, IF ANYI

TITLE \_\_ Engineering Secretary

4-9-82

OIL AND GAS INSPECTOR

APR 1 3 1982