

STATE OF NEW MEXICO.
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

JUN 7 1982

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐

GAS WELL ☒

OTHER-

Name of Operator

Yates Petroleum Corporation ✓

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 6S RANGE 25E NMPN

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

LG-4333

7. Unit Agreement Name

8. Form or Lease Name

Skinny QO State

9. Well No.

3

10. Field and Pool, or Wildcat

Pecos Slope Abo

11. Elevation (Show whether DF, RT, GR, etc.)

3929.4' GR

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 7:00 PM 5-30-82. Ran 24 joints of 8-5/8" 24# J-55 casing set at 923'. 1-Type "M" notched guide shoe at 923'. Insert float at 883'. Cemented w/500 sacks Halliburton Lite, 1/4# flocele and 2% CaCl₂. Tailed in w/200 sacks Class "C" 2% CaCl₂. Comprssive strength of cement - 1250 psi in 12 hours. PD 8:30 PM 5-31-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 2:30 PM 6-1-82. WOC 18 hours. Nipped up and tested to 1000 psi, okay. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Virginia Goodlett

TITLE Engineering Secretary

DATE 6-7-82

APPROVED BY Mike Welton

TITLE OIL AND GAS INSPECTOR

DATE JUN 11 1982

CONDITIONS OF APPROVAL, IF ANY: