

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

JUL 15 1982

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5c. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
LG-4333

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPLN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM

THE West LINE, SECTION 16 TOWNSHIP 6S RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Skinny QO State

9. Well No.
3

10. Field and Pool, or Wildcat
Und. San Andres

15. Elevation (Show whether DF, RT, GR, etc.)
3929.4' GR

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

DRILL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Plugback to test San Andres

☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged back well as follows:

Plug #1: 50 sacks Class "C" Neat plug from 3750-3650'. PD 8:30 PM 6-7-82

Plug #2: 50 sacks Class "C" Neat plug from 1750-1650'. PD 9:20 PM 6-7-82

Ran 26 joints of 4-1/2" 10.5# J-55 casing at 1600'. 1-regular guide shoe at 1600'. Float collar at 1558'. Used 250 gallons of mud flush ahead of cement. Cemented w/ 300 sacks 50/50 Poz with 6# salt. Compressive strength of cement - 1050 psi in 12 hours. PD 2:10 PM 6-8-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 25 sacks to pit. WOC. WIH and perforated 1397-1407' w/11 .50" holes. Spot acid across perforations 1397-1407' w/500 gallons 7 1/2% NE acid and 10 balls.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *James L. Bonnell*

TITLE Engineering Secretary

DATE 7-15-82

APPROVED BY

Michael W. Miller

TITLE OIL AND GAS INSPECTOR

DATE JUL 16 1982

CONDITIONS OF APPROVAL, IF ANY: