

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☒
2. NAME OF OPERATOR  
McClellan Oil Corporation ✓
3. ADDRESS OF OPERATOR  
P. O. Drawer 730, Roswell, NM 88202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Casing and Cement

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
FEB 18 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM-28306 RECEIVED
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME FEB 24 1982
8. FARM OR LEASE NAME O. C. D.  
Coyote Draw Federal ARTESIA, OFFICE
9. WELL NO.  
2
10. FIELD OR WILDCAT NAME  
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 6-T8S-R25E
12. COUNTY OR PARISH Chaves 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3740' G.L.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/09/82: Drilled 80' of 24" hole. Ran 80' of 20" conductor pipe. Cemented with 5 yards Ready-Mix.

2/11/82: Move in Tex-Mex Rig #1.

2/12/82: Spudded at 7:00 P.M. 2/11/82

2/13/82: TD at 606' with 17½" bit. Ran 580' of 13-3/8", 54 lb/ft casing. Cemented with 650 sx Class "C" with 2% CaCl<sub>2</sub> and 100 sx Thix-Set with 2% CaCl<sub>2</sub>. Did not circulate cement. TOC at 100'. One inched with 127 sx Class "C" neat. Circulated 20 sx. WOC - 18 hours.

2/14/81: Resume drilling with 12-1/4" bit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE Engineer DATE 2/16/82

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL \_\_\_\_\_

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side