

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Berge Exploration, Inc.

3. ADDRESS OF OPERATOR
7100 N. Broadway, Ste. 2-E, Denver, CO 80221

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1980/S 660/W

AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Change Plans

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC-067811-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dale Federal

9. WELL NO.

#13

10. FIELD OR WILDCAT NAME

Undesignated ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T. 7S, R. 26E

12. COUNTY OR PARISH 13. STATE

Chaves New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3748' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Per verbal approval - Change plans to run 780' of 8-5/8" 24# J-55 casing @ surface instead of 900' of 8-5/8" 24# J-55 casing.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Brian Schmitt TITLE Agent

DATE 4/20/82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAY 12 1982

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side