

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NM OIL GULB. CO. LEASE  
Prior DD  
Artesia, NM 88210

NM 022584

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

STEVENS OPERATING CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 2408, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FNL 1980 FWL Sec 28 T7S R26E

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Perf ☐

SUBSEQUENT REPORT OF:

☐

☒

☒

☐

☐

☐

☐

☐

☒

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME

Sun Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME ARTESIA, OFFICE

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T7S, R26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

30-005-61351

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3706.2 GR

(NOTE: Report results of well deepening on Form 9-330.)

RECEIVED  
MAR 29 1983

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give surface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-17-83 Trip out of hole w/tubing. Perf w/Dresser @ 4202, 21, 22, 23 (2 SPF - 0.31) 16 shots total.

3-18-83 Ran RBP & packer. Set RBP @ 4236', set packer @ 4168' & acidize w/3000 gal. 7 1/2% Abo acid and 1000 SCF N<sub>2</sub>.

3-19-83 Frac via 2 3/8" tubing w/20,000 gal Yf4 CO<sub>2</sub> and 15,000# 20/40 sand and 20,700# 10/20 sand.

3-23-83 Pull packer out of hole & trip in w/on-off tool. Ran 138 joints 2 3/8" and set seating nipple @ 4168'.

Verbal approval was obtained from Pete Chester on 3/15/83.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Production

SIGNED

TITLE Controller

DATE March 28, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 6 1983

\*See Instructions on Reverse Side

ROSWELL, NEW MEXICO