

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artesia, NM 88210

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Cement and Casing ☐

5. LEASE

NM-28306

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Coyote Draw Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Wildcat Und. W.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 30-T7S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3778' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/09/82: Drilled 40' of 24" hole with Link Rat Hole.

2/10/82: Move in Salazar Rig #14.

2/11/82: Spud with 17-1/2" bit. Drilled to 400'. Reduced bit size to 12-1/4".

2/18/82: TD at 1367'. Ran 1367' of 8-5/8", 23# new casing. Cemented with 765 sx Halliburton Light with 1/4# Flocele and 300 sx Class "C" with 2% CaCl₂. Circulated 45 sx. WOC - 18 hours. Nipple up wellhead. Pressure test to 1000 psi for 30 minutes.

2/19/82: Drill out with 7-7/8" bit.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

TITLE Engineer

DATE 2/22/82

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

TITLE

DATE