

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
C/SF GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Casing and Spud

SUBSEQUENT REPORT OF:



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM-28306

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME  
Coyote Draw Federal

MAR 11 1982

9. WELL NO.

4

O. C. D.

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Wildcat Und. Zone

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 31-T7S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3702' G.L.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/28/82: Set 60' of 20" conductor pipe. Cemented with 5 yards Ready-Mix. Move in Salazar Rig #14. Spud with 12-1/4" bit. Reamed hole with 17-1/2" bit to 289'.

3/01/82: Ran 281' of 13-3/8" 54# new casing. Cemented with 100 sx Thix-Set and 300 sx Class "C" with 2% CaCl<sub>2</sub>. Did not circulate cement. WOC - 6 hours. Ran temperature survey - TOC - 115'.

3/02/82: One inched cement to surface with 250 sx Class "C" with 2% CaCl<sub>2</sub> in 3 stages. WOC - 4 hours. Drill out with 12-1/4" bit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineer DATE 3/02/82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAR 10 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO