

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYDrawer DD  
Artesia, NM 88210

## 5. LEASE

NM-28306

RECEIVED

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## 7. UNIT AGREEMENT NAME

APR 2 1982

## 8. FARM OR LEASE NAME

Coyote Draw Federal ARTESIA, OFFICE

## 9. WELL NO.

4

## 10. FIELD OR WILDCAT NAME

Wildcat Und. Also

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31-T7S-R25E

## 12. COUNTY OR PARISH

Chaves

## 13. STATE

NM

## 14. API NO.

## 15. ELEVATIONS (SHOW DF, KDB, AND WD)

3702' G.L.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

## 2. NAME OF OPERATOR

McClellan Oil Corporation/

## 3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, N.M.

## 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL &amp; 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

## 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐

(other) Casing and cement

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐RECEIVED  
MAR 19 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3/08/82: Drilled to 1400' with 12 1/4" bit. Ran 1400' of 8-5/8", 23# casing. Cemented with 450 sx Halliburton Lite with 2% CaCl<sub>2</sub> and 200 sx Class "C" with 2% CaCl<sub>2</sub>. Did not circulate cement. WOC - 6 hours TOC @ 480'. One inched cement to surface with 300 sx Class "C" with 2% CaCl<sub>2</sub> and 500 gal. Flo-chek in 3 stages. WOC - 4 hours. Nipple up wellhead. Test casing to 500 psi for 30 min. Resume drilling with 7-7/8" bit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

## 18. I hereby certify that the foregoing is true and correct

SIGNED

Paul Hagihole

TITLE

Engineer

DATE

3/15/82

APPROVED FOR RECORD (This space for Federal or State office use)

APPROVED BY ROYAL A. CHAPMAN  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 19 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side