

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
Drawer DD NM 88210

NM OIL CONS. COMMISSION
Drawer DD NM 88210

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL & 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) SPUD, 13 3/8" CSG & CEMENT

SUBSEQUENT REPORT OF:

RECEIVED
FEB 8 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE NM 40029
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
ALKALI FED COM
9. WELL NO.
0
10. FIELD OR WILDCAT NAME
UNDESIGNATED ABO
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC 34, T5S, R25E
12. COUNTY OR PARISH
CHAVES
13. STATE
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3689' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 2-1-82. Drilled to 706' (tight hole) and ran 17 jts 13 3/8", 48#, H-40 casing set at 705'. Cemented with 700 sx HLW + 1# flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 3:30 PM 2-2-82. Cement did not circulate. Ran temp survey - TOC at 190'. Set seven plugs with a total of 1100 sx "C" + 4% CaCl + 300 gals flochek to circulate cement. WOC 9 hours, blew hole dry and waited one hour no fluid. Reduced hole to 12 1/4" and drilled ahead on 2-4-82. WOC total of 35 hours.

XC: USGS (G), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ REGULATORY COORDINATOR DATE 2-4-82

ACCEPTED FOR RECORD
ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

