

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

c/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
MESA PETROLEUM CO. ✓
3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) 8 5/8" CSG & CEMENT

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM 40029
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
ALKALI FED COM
9. WELL NO.  
11
10. FIELD OR WILDCAT NAME  
UNDESIGNATED: ABO
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
SEC 34, T5S, R25E
12. COUNTY OR PARISH  
CHAVES
13. STATE  
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3675' GR

RECEIVED

MAR 12 1982

O. G. D.

ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole on mist to 1784'. Ran 43 jts 8 5/8", 24#, K-55 casing set at 1784'. Cemented with 700 sx Thixalite + 1/4# Flocele + 4% CaCl and tailed in with 300 sx "C" + 2% CaCl. PD at 9:00 AM 3-3-82. Circulated 125 sx. Tested BOPs and casing to 600 psi for 30 mins - OK. Reduced hole to 7 7/8" and drilled ahead on 3-4-82. WOC total of 18 1/2 hours.

XC: <sup>mms</sup> ~~USGS~~ (6), TLS, CEN RCDS, ACCTG, MEC, REM, PARTNERS, ROSWELL, FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard E Mathis REGULATORY COORDINATOR DATE MARCH 4, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAR 11 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

