

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

FEB 11 1982

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TEST FOR GAS PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

Oil Well ☐ Gas Well ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Name of Well

UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM

THE East LINE, SECTION 2 TOWNSHIP 8S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3614' GR

10. Indicate Type of Lease

State ☒ For ☐

11. State Oil & Gas Lease No.

LG 679

12. Unit Agreement Name

13. Farm or Lease Name

Rook RK State

14. Well No.

2

16. Field and Pool, or Wildcat
Und. Abo

17. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
VENT A WELL ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

18. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 30' of 20" conductor pipe. Spudded a 14-3/4" hole at 1:15 PM 1-29-82. Ran 21 joints of 10-3/4" 40.5# casing set at 850'. 1-Notched guide shoe set at 850'. Insert float at 810'. Cemented w/500 sacks Halliburton Lite and 2% CaCl₂. Tailed in w/200 sacks Class "C" 2% CaCl₂. PD 3:00 PM 2-1-82. Bumped plug to 750 psi, released pressure and float held okay. WOC. Drilled out 11:15 AM 2-2-82. WOC 20 hours and 15 minutes. Nipped up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Circ 50 SX

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Engineering Secretary

TITLE Engineering Secretary

DATE 2-9-82

PROVED BY Oil and Gas Inspector

TITLE OIL AND GAS INSPECTOR

DATE FEB 15 1982

CONDITIONS OF APPROVAL, IF ANY: