APPLICATION FOR PERMIT TO DRILL

MESA PETROLEUM CO. CHARLOTTE FEDERAL #4 1650' FSL & 1980' FWL, SEC 30, T7S, R26E CHAVES COUNTY, NEW MEXICO

LEASE NO. NM 16324

In conjunction with Form 9331-C, Application For Permit to Drill subject well, the following additional information is provided:

- 1. Applicable portions of the <u>GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL LEASES</u>, Roswell District, Geological Survey of September 1, 1980 will be adhered to.
- 2. Geological markers are estimated as follows:

SEVEN RIVERS	Surface
SAN ANDRES	460'
GLORIETA	1397'
TUBB	2988'
ABO	3660'

- 3. Hydrocarbon bearing strata may occur in the Abo formation(s). No fresh water is expected to be encountered below 900'.
- 4. The Casing and Blowout Preventer Program will be determined by hole conditions as encountered. See Exhibit VI. Anticipate drilling with air or foam using ram type preventer and rotating head for well control. The 13 3/8" casing will be set at approximately 900' to protect any fresh water zones and cemented to the surface. The 85/8" casing will be set at approximately 1600' if water zones have been encountered or omitted if not and ram type preventers installed. Sufficient amounts and kinds of cement would be used to ensure any water, gas, or oil zones encountered are isolated and shut off down to the casing point if run. The 41/2" production casing will be set at total depth or shallower depending upon the depth of the deepest commercial hydrocarbon bearing strata encountered.
- 5. No drill stem test or coring program is planned. The logging program may consist of a GR-CNL from surface total depth and FDC from casing point to total depth.
- 6. Anticipated drilling time is ten days with completion operations to follow as soon as a completion unit is available.