NM OIL UNS. COMMISSION Drawer DD

Artesia, NN 88210

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

0.1	<	F
$\mathcal{O}_{\mathcal{I}}$	J	Г

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

DEPARTMENT OF THE INTERIOR C/SF GEOLOGICAL SURVEY	5. LEASE NM 9982 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME FEB 2 5 1982	
1. oil gas well other	Teckla MD Federal 9. WELL NO. O. C. D.	
 NAME OF OPERATOR Yates Petroleum Corporation ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980 FSL & 660 FWL, Sec. 12-6S-25E AT SURFACE: AT TOP PROD. INTERVAL: 	10. FIELD OR WILDCAT NAME Pecos Slope-Abo Gas 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit L. Sec. 12-6S-25E 12. COUNTY OR PARISH Chayes NM 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3837.8 GR	
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF		

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 40' of 20" conductor pipe. Spudded a 14-3/4" hole at 11:00 AM 2-11-82. Ran 23 joints of 10-3/4" 40.5# casing set at 907. Insert float at 880. Cemented w/400 sacks Pacesetter 2% CaCl $_2$ and 300 sacks Class "C" 2% CaCl $_2$. PD 4:00 AM 2-13-82. Bumped plug to 750 psi, released pressure and float held okay. WOC. Circulated 50 sacks to pit. Drilled out 10:00 PM 2-13-82. WOC 18 hours. Nippled up and tested to 1000 psi, OK. Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type DIL & GAS.. Set @ ___ U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO 18. I hereby certify that the foregoing is true and correct CALLY TITLE Engineering Secty DATE SIGNED. ACCEPTED FOR RECORD (This space for Federal or State office use) ROGER A. CHAPMAN

PPROVED BY

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

.. TITLE

DATE