

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Clements Energy Inc		Lease Reid		Well # 1-Y	
Location of Well	Unit 19803 155E	Section 20	Township 14	Range 26	County Chaves
Drilling Contractor Cactus Drilling			Type of Equipment Rotary 1-29-82		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8"	48#		400'	400 SX Circ
12 1/4	8 5/8"	24#		1350'	600 SX Circ
7 7/8	5 1/2"	15.5#		7050'	750 SX

Casing Data:

Surface joints of 8 5/8 inch 24 # Grade J-55
 Yes (Approved) (Rejected)

Inspected by BW Weaver date 2-4-82

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required

Type of Shoe used Guide Float collar used Float collar Btm 3 jts welded yes

TD of hole 1350 Set 1369 Feet of 8 5/8 inch 24 # Grade J-55

New ~~used~~ csg. @ 1369 with 200 sacks neat cement around shoe

+ 450 sax Henco lite additives 5 Gelsolve 1/4 FloSeal 2% Grain Check

Plug down @ 6:00 (AM) (PM) Date 2-4-82

Cement circulated yes No. of Sacks 50

Cemented by Henco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break @ 1146 2 Centrifuges