

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Mesa Petroleum Co</u>		Lease <u>Neal Corn</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980W 660W</u>	Section <u>5</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor <u>Dual Drilling</u>			Type of Equipment <u>Rotary 4-15-82</u>		

*Witnesses

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>		<u>900'</u>	<u>800 SX Circ</u>
<u>11 or 12 1/4</u>	<u>8 5/8</u>	<u>24 #</u>		<u>1600'</u>	<u>800 SX</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>10.5 #</u>		<u>4450</u>	<u>1000 SX</u>

Casing Data:

Surface 23 joints of 10 3/4 inch 40.5 # Grade J-55

Yes (Approved) (Rejected)

Inspected by BW Weaver date 6-18-82

Cementing Program

Size of hole 14 3/4 Size of Casing 10 3/4 Sacks cement required 200

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 902 Set 904 Feet of 10 3/4 Inch 40.5 # Grade J-55

New-used csg. @ 900 with 200 sacks neat cement around shoe

+ 700 sax Hawcolite additives

Plug down @ 9.00 (AM) (PM) Date 6-18-82

Cement circulated yes No. of Sacks 100

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 3 Centralizers Last Drilling Break 723 ft