

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

015F
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
Stevens Operating Corporation

3. ADDRESS OF OPERATOR
P. O. Box 2408, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1980' FSL & 660' FEL, Sec 20-T6S-
AT SURFACE: R23E
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Casing and Cement Record

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
MAR 25 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM 32324 **RECEIVED**
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME **MAY - 6 1982**

8. FARM OR LEASE NAME **O. C. D.**
M & M Federal **ARTESIA, OFFICE**
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Undesignated *Abc.*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC 20-T6S-R23E
12. COUNTY OR PARISH **Chaves** 13. STATE **NM**
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/27/82 Tex Mex Rig #3 rig up and spud at 3:30 pm.

3/1/82 Ran 16 joints 13 3/8". Set and cement at 604' w/600 sks 65/35 POZ and 200 sks Class C w/2% CaCl₂. Plug down at 2:30 pm. Circulate 0 sks cement. Ran temp survey, indicated cement at 520'. Ran 500' 1" set w/50 sk plug, SD 2 hrs, tag cement at 380', ran 2 more 75 sk plugs tag at 280'. Pumped 400 sks cement down annulus, circulated to surface.

3/4/82 Ran 38 joints 8 5/8" 24.0# casing. Set and cement at 1528' w/1300 sks POZ cement. Plug down at 6:45 am, circulated 40 sks.

3/11/82 Ran 87 joints 4 1/2" 10.5# casing. Set and cement at 3550' w/350 sks Self Stress. Plug down at 11:35 am.

Subsurface Safety Valve: Manu. and Type _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Car Thompson* TITLE Prod. Coordinator DATE March 24, 1982

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO
DATE **MAY 5 1982**