		NH OIL COMB. COMME	Form Ap		
Form 9-331 Dec. 1973		Artesia, NM 88210		Bureau No. 42-R1424	
	UNITED STATI		5. LEASE NM 32324		
DI C/SE	EPARTMENT OF THE GEOLOGICAL SUI		6. IF INDIAN, ALLOTTEE O	R TRIBE NAME RECEIVED	
		PORTS ON WELLS	7. UNIT AGREEMENT NAM	1E	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)			8. FARM OR LEASE NAME	MAY - 6 1982	
	gas 🛛 other		M & M Federal 9. WELL NO.	 O. C. D	
	well ether		2 9. WELL NO.	ARTESIA, OFFICE	
2. NAME OF OPERATOR Stevens Operating Corporation			10. FIELD OR WILDCAT NA	ME	
3. ADDRESS OF OPERATOR			Undesignated al		
P. O. Box 2408, Roswell, NM 88201			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17			SEC 20-T6S-R23E		
below.) AT SURFACE: 10901 pet 6601 FFT. SEC 20-T65-				13. STATE	
AT SURFACE: 1980' FSL, 660' FEL, SEC 20-T6S- AT TOP PROD. INTERVAL: R23E			Chaves	NM	
AT TOTAL DEPTH: same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			14. API NO.		
16. CHECK APPI REPORT, OR	ROPRIATE BOX TO INDI	CATE NATURE OF NOTICE,	15. ELEVATIONS (SHOW	DF, KDB, AND WD)	
REQUEST FOR A TEST WATER SH FRACTURE TREA SHOOT OR ACIE REPAIR WELL PULL OR ALTER MULTIPLE COMP CHANGE ZONES		IBSEQUENT REPORT OF:		602 D 1982 ЛЦ ОН 8 GAS	
ABANDON*				OLOGICAL SURVEY	
17. DESCRIBE		ED OPERATIONS (Clearly sta any proposed work. If well is all markers and zones pertine	ate all pertinent details, and directionally drilled, give subs	give pertinent dates,	
3-20-82	Perforated at 29 66, 68.5, 69, 69	944.5, 45, 45.5, 46, 9.5, 75.5, 76, 77.5,	48.5, 49, 49.5, 53 78.	.5, 54, 65.5,	
3-23-82	-23-82 Ran 91 joints of 2 3/8" tubing and baker lock set packer at 2878'. Acidized w/3000 gallons 7½% HCL and 25 balls, pressure 1500#, avg rate 4/bpm, ISIP 1000#, frac gr .77.				
3-24-82 Frac thru 4 ¹ ₂ " w/63000 gal YF6 water, 2400# J347 gel, 80 gal F75 2/1000, 400 # M3 200 per tank, 3 drums E120, 1 drum E1175, 6 gal E1208, 118000# 20/40, 29000# FLA100, 44000# 10/20, 39200 gal Y16 PSD and 87 tons water.					
Subsurface Safe	ety Valve: Manu. and Type			@ Ft.	
18. Litereby cel	rtify that the foregoing is t	rue and correct	FOR RECOR		
SIGNED The	Mompre	TITLE Prod Coordin	ACCEPTED FOR RECON	6 24 1982	
	1/	(This space for Federal or State	office use)		
APPROVED BY	V	TITLE	ENTE		
CONDITIONS OF	APPROVAL, IF ANY:		U.S. GEOLOGICAL S ROSWELL, NEW MI	EXICO	
		_	RUSWE		

*See Instructions on Reverse Side