

686 ft @ 350

3-4 MIN F1

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Peapack "OI" State</u>		Well # <u>3</u>	
Location of Well	Unit <u>EC</u>	Section <u>16</u>	Township <u>7</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor <u>Horizon</u>	Type of Equipment <u>Rotary</u>				
*Witness <u>guided 3/21/82</u>					
APPROVED CASING PROGRAM					

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12 3/4	10 3/4	40.5# J-55		900'	750 sx - Circ
7 7/8	4 1/2	9.5# J-55		4250 TD	350 sx Circ

Casing Data:

Surface 23 joints of 10 3/4 inch 40.5 # Grade J-55

(Approved) (Rejected)

Inspected by Brown date 3-23-82

Cementing Program

Size of hole 12 3/4 Size of Casing 10 3/4 Sacks cement required 200Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded YesTD of hole 925 Set 927 Feet of 10 3/4 Inch 40.5 # Grade J-55New ~~used~~ csg. @ 927 with 300 sacks neat cement around shoe+ 400 sax Pace Setter ltc additives 3% CCPlug down @ 1:30 (AM) (PM) Date 3-23-82Cement circulated Yes No. of Sacks 500 sxCemented by Western Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break 620