

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

MAR - 5 1982

O. C. D.
ARTESIA, OFFICEForm C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
2. State Oil & Gas Lease No. LG-0336	
3. Unit Agreement Name	
4. Farm or Lease Name Redman OY State	
5. Well No. 4	
6. Field and Pool, or Wildcat Undesignated Apo	
7. Elevation (Show whether DF, RT, GR, etc.) 3998'	
8. County Chaves	

9. Name of Operator
Yates Petroleum Corporation /

10. Address of Operator
207 South 4th St., Artesia, NM 88210

11. Location of Well
UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM
THE West LINE, SECTION 35 TOWNSHIP 4S RANGE 24E NMPM.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 40' of 20" conductor pipe. Spudded a 14-3/4" hole at 3:30 PM 2-28-82. Ran 23 joints of 10-3/4" 40.5# J-55 ST&C casing set at 922'. 1-Texas Pattern guide shoe at 922'. Insert float at 881'. Cemented w/500 sacks Howco Lite, 2% CaCl₂. Tailed in w/250 sacks Howco "C" 2% CaCl₂. PD 2:00 PM 3-2-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. Drilled out 8:00 AM 3-3-82. WOC 18 hours. Nippled up and tested to 1000#, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ISSUED <i>[Signature]</i>	TITLE Engineering Secretary	DATE 3-5-82
APPROVED BY <i>[Signature]</i>	TITLE OIL AND GAS INSPECTOR	DATE MAR 9 1982
CONDITIONS OF APPROVAL, IF ANY:		