

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL & 1980 FEL, Sec. 21-7S-25E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Production Casing, Perforate

LEASE

NM 28304

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Albitus TH Federal

9. WELL NO.

10. FIELD OR WILDCAT NAME

11. Pecos Slope Abo

12. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Unit B, Sec. 21-T7S-R25E

13. COUNTY OR PARISH 13. STATE

Chaves NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3766.2' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4153'. Ran 103 joints of 4-1/2" 9.5# K-55 LT&C casing set at 4153'. 1-regular guide shoe set at 4153'. Auto fill float collar set at 4116'. Cemented w/650 sacks Howco 50/50 Poz and .3% Halad-4 with .3% CFR-2 and 2# KCL with 2% gel. PD 3:15 AM 3-29-82. Bumped plug to 1350 psi, released pressure and float held okay. WOC. WIH and perforated 3624-3880' w/14 .40" holes as follows: 3624, 25, 26, 28, 29, 30, 3874, 75, 76, 77, 78, 79 and 3880'. Note: Misperforated 3674-80' w/7 .40" holes. Squeezed perfs 3674-80' w/25 sacks Class "C" cement. Squeezed to 2200#. WOC 24 hours. Drilled out 11:00 AM 4-8-82. Test cement squeeze to 2500# for 10 minutes. Frac'd perfs 3624-30' w/1000 gallons 7 1/2% acid, 20000 gallons KCL and 40000# 20/40 sand. Frac'd perfs 3874-80' w/1000 gallons 7 1/2% acid, 20000 gallons KCL and 40000# 20/40 sand. Well stabilized at 20 psi on 3/4" choke = 480 mcfpd.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineering Secty DATE 4-20-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

APR 27 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side