including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 3-8-82. Drilled with ធ្លើរដ្ឋាភិបាន and ran 20 jts 13 3/8", 48#, H-40 casing set at 817'. Cemented 与点对 10 多数 Thixalite + 1/4# Flocele + 4% CaCl and tailed in with 30\% &x 200 " + 22% = PD at 4:00 a.m. 3-9-82. Circulated 200 sx. Blew hole are and see and see are all lates and dealers are all lates and dealers. wainted I hour-no fluid. Reduced hole to 12 1/4" and drill自由最高的 and drill自由 3-10-82. WOC total of 19 hours.

WISKS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL 45 Subsurface Safety Valve: Manu. and Type ... 18. I hereby certify that the foregoing is true and correct

TIREGULATORY COORDINATORATE SIGNED

(This space for Federal or State office use)

A CEPTED FOR RECORD APPROVED BY CONDITIONS OF APPROVAL, GETANN MAN

Form 9-331

Dec. 1973

CISF

well

below.)

FRACTURE TREAT SHOOT OR ACIDIZE

REPAIR WELL

CHANGE ZONES

ABANDON*

(other)

AT SURFACE:

gas

well

DATE

Areal colling of colling of the coll

3 8

MAR 1 9 1982

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY POTATU, NEW MEXICO