

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to produce a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐2. NAME OF OPERATOR  
Stevens Operating Corporation3. ADDRESS OF OPERATOR  
P. O. Box 2408, Roswell, NM 882014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660 FNL, 660 FEL, Sec 13, T8S, R25E  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud, casing ☐

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐5. LEASE  
NM 294176. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A7. UNIT AGREEMENT NAME  
N/A8. FARM OR LEASE NAME  
Paul-Hicks Federal9. WELL NO.  
210. FIELD OR WILDCAT NAME  
Wildcat11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 13, T8S, R25E12. COUNTY OR PARISH  
Chaves13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3563.0 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 16 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-3-82 Tex Mex Rig #4 spud at 12:00 noon w/12½" bit.

4-5-82 Ran 20 joints 8 5/8" 24# csg, set and cement at 895' w/300 sxs 65/35 POZ and 200 sxs Class C w/2% CaCl<sub>2</sub>. Plug down at 9:00 am, circ 95 sxs, pressure up 1000# for 30 min, plug held.4-15-82 Ran 112 jts 4½" 10.5# csg, set and cement at 4536' w/360 sxs Self Stress and 2% CaCl<sub>2</sub>. Plug down at 11:45 am, pressured up 1000# for 30 minutes, plug held.

XC: MMS(orig + 6), Partners, File

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Laurie Kessel TITLE Prod Clerk DATE 4/15/82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 17 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO