

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <b>Yates Petroleum Corp</b>		Lease <b>Rook "R&amp;K" State</b>		Well # <b>3</b>	
Location of Well	Unit <b>16505 below L</b>	Section <b>2</b>	Township <b>8</b>	Range <b>25</b>	County <b>Chaves</b>
Drilling Contractor	<b>Horizon Drllg</b>		Type of Equipment <b>Rotary</b>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4	40.5# J-55		875	550 sx Circ
7 7/8"	4 1/2	10.5#		4225	350 sx -

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 14 3/4 Size of Casing 10 3/4 Sacks cement required 150

Type of Shoe used Tex Pat Float collar used Incent Btm 3 jts welded Yes

TD of hole 875 Set 885 Feet of 10 3/4 Inch 40.5 # Grade J-55

New ~~used~~ csg. @ 885 with 300 sacks neat cement around shoe

+ 400 sax Pace Lts Lite additives + 100 SX Thick set

Plug down @ 9.00 (AM) (PM) Date 3-10-82

Cement circulated yes No. of Sacks 150

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_