

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 120
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Skink "SK" State</u>		Well # <u>4</u>	
Location of Well	Unit <u>1920W 1920W F</u>	Section <u>36</u>	Township <u>7</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor <u>Stewart Bros?</u>			Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>14 3/4</u>	<u>10 3/4</u>	<u>40.5# J-55</u>		<u>850'</u>	<u>630 sk Circ</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>9.5#</u>		<u>3150'</u>	<u>350 sk</u>

Casing Data:

Surface _____ joints of 10 3/4" inch 40.5# Grade J-55
(Approved) (Rejected)

Inspected by M.S. date 3/10/82

Cementing Program

Size of hole 14 3/4" Size of Casing 10 3/4" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 850' Set 850' Feet of 10 3/4" inch 40.5# Grade _____

New used csg. @ 850' with 300 2%a sacks neat cement around shoe

+ 400 sack facella lite additives (470cc)

Plug down @ 7845 (AM) (PM) Date 3/12/82

Cement circulated yes No. of Sacks 40 sk

Cemented by Western Co. Witnessed by Miss Stillefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

No centralizers or spacers

Full returns to TD.