

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

c/sf
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Jack Grynberg and Associates

3. ADDRESS OF OPERATOR
1050 17th Street, Suite 1950, Denver, CO 80265

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 660' FWL of Sec. 12
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Laid Casing</u>		

5. LEASE
USA-NM-11795

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Hobbs Canyon Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME
Und. Pecos Slope Abo Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T 6 S - R 24 E

12. COUNTY OR PARISH
Chaves

13. STATE
NM


14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4017.0' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/25/82 Ran 95 jts 10.5# J-55 4 1/2" csg. set @4024'. Ran 500 gals of mud flush ahead of 2000 sxs 5050 POZ, 2% gel, 6# salt, 3/10ths of 1% Halid 4, 3/10ths of 1% CFR2. Top of cmt @908'.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED NANCY STOLZLE TITLE LAND MANAGER DATE 3/26/82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD 3/26/82
APR 28 1982
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO