

C/SF

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

O. C. D.

2. NAME OF OPERATOR ARTESIA, OFFICE

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FSL & FEL, Sec. 35-5S-24E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
MAY 25 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE NM 30391
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Grafa RW Federal
9. WELL NO. 2
10. FIELD OR WILDCAT NAME
Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit P, Sec. 35-T5S-R24E
12. COUNTY OR PARISH 13. STATE
Chaves NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3926' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole 7:00 PM 5-4-82. Set 40' of 20" conductor pipe. Ran 23 joints of 10-3/4" 40.5# J-55 casing set at 930'. 1-Texas Pattern guide shoe set 930'. Flapper insert float set 890'. Cemented w/400 sacks Halliburton Lite with 2% CaCl. Tailed in w/200 sacks Class "C" 2% CaCl. Compressive strength of cement - 1365 psi in 12 hours. PD 9:00 PM 5-5-82. Bumped plug to 500 psi, released pressure and float held okay. Circulated 40 sacks to pit. WOC. Drilled out 3:00 PM 5-6-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED James A. Bodette TITLE Engineering Section

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
MAY 27 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO