

UNITED STATES

DEPARTMENT OF THE INTERIOR

C/SF

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
660 FNL & FEL, Sec. 4-8S-25E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

SUBSEQUENT REPORT OF:

- ☒
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED
MAR 18 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM 9539
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Williamson LC Federal
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
Und. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit A, Sec. 4-T8S-R25E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3577' GR

RECEIVED

APR 2 1982

O. C. D.
ARTESIA, OFFICE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 40' of 20" conductor pipe. Spudded a 14-3/4" hole at 7:45 PM 3-8-82. Ran 22 joints of 10-3/4" 40.5 ST&C casing set at 887'. 1-Texas Pattern notched guide shoe set at 887'. Insert float at 847'. Cemented w/700 sacks Halliburton Lite, 2% CaCl₂. Tailed in w/200 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 800 psi in 12 hours. PD 9:30 AM 3-10-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 5:30 AM 3-11-82. WOC 20 hours. Nipped up and tested to 1000 psi, okay. Reduced hole to 9-7/8" to approximately 1650', then will reduce hole to 7-7/8" to TD. Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Engineering Secty DATE 3-17-82

(This space for Federal or State office use)

APPROVED BY _____
CONDITION _____

TITLE _____ DATE _____

MAR 19 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side