Form 9-331 Dec. 1973 Artesia, NM 8823	 ၂၀ Form Approved. • ပံု Budget Bureau No. 42–R1424
UNITED STATES	5. LEASE NM-16324
c/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME EIVED
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME MAY - 6, 1982
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME CHARLOTTE FED COM O. C. D
1. oil gas well well a other 2. NAME OF OPERATOR	9. WELL NO. ARTESIA, OFFICE
MESA PETROLEUM CO./	10. FIELD OF WILDCAT NAME UNDESIGNATED ABO
<ul> <li>ADDRESS OF OFERATOR</li> <li>1000 VAUGHN BUILDING/MIDLAND TX 79701-4493</li> <li>4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> <li>1980' FNL &amp; 660' FWL</li> </ul>	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC 29, T7S, R26E
AT SURFACE: AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH CHAVES13. STATE NEW MEXICO
AT TOTAL DEPTH: SAME 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3573' GR
REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)

ب د دو ا

A .....

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to drill 14 3/4" hole with air or mud to approximately 950' and run 10 3/4" casing. Will cement to surface and test to 600 psi with cement head. Will then reduce hole to  $9\frac{1}{2}$ " and drill to approximately 1600'. If circulation has not been lost, will reduce hole to 7 7/8", nipple up BOP's and test to 600 psi and drill to TD. If circulation has been lost, will run 7 5/8" casing and tie back to 10 3/4" casing with cement. Will then reduce hole to  $6\frac{1}{2}$ " or  $6\frac{1}{4}$ ", nipple up BOP's and test, and drill to TD.

XC: MMS (6), TLS, CEN RCD Subsurface Safety Valve: Manu. and Type	S, ACCTG, MEC, REM, PARTNERS	ACCEPTED FOR RECORD , ROSWEIL Set @000
<b>18.</b> I hereby certify that the foregoing is the signed $R$ is $M$ in the foregoing in the signed $R$ is a signed of the signed	rue and correct	APR 2 7 1982 3-25-82 GEOLOGICAL SURVEY
APPROVED BY		ROSWELL, NEW MEXICO
	•See Instructions on Reverse Side	MAR 89 1382

U.S. GEOLOGICAL SURVEI ROSWELL, NEW MEXICO