

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

OCT 19 1982

2. NAME OF OPERATOR
STEVENS OPERATING CORPORATION

O. C. D.

3. ADDRESS OF OPERATOR

P. O. Box 2408, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990 FNL, 1980 FEL, Sec 23, 7S, 26E

AT TOP PROD. INTERVAL: same as above

AT TOTAL DEPTH: same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

☐

FRACTURE TREAT ☐

☐

SHOOT OR ACIDIZE ☐

☒

REPAIR WELL ☐

☐

PULL OR ALTER CASING ☐

☐

MULTIPLE COMPLETE ☐

☐

CHANGE ZONES ☐

☐

ABANDON* ☐

☐

(other) perforations

5. LEASE

NM 27634

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

HANAGAN FEDERAL

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 23, T7S, R26E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3812.2 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-28-82 Ran 124 jts 4 1/2" 10.5# csg, set and cement at 5038' (PBDT 4996') w/520 sxs Self Stress and 2% CaCl₂. WOC 18 hrs. Pressure up 1000# logging no pressure decrease.

6-03-82 Perf. at 4474, 74.5, 76, 77, 77.5, 78, 4541, 41.5, 42, 45, 48, 48.5, 49, 49.5, 50, 50.5, 4554, 54.5, 55.

6-04-82 Ran 144 jts 2 3/8" 4.7# tbgs, set packer at 4387' (78' above top perf)

6-05-82 Acid w/4500 gal nitroified 7 1/2% HCL and 30 ball sealers, avg trtg press 2400#, avg rate 7.2 BPM, max trtg press 2800#, max rate 7.4 BPM, ball out at 3800#, ISIP 2350#.

6-08-82 Pull packer out of hole. Ran 144 jts 2 3/8" tbgs, set at 4387'.

XC: MMS (orig + 6), File, Partners ()

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Pat. Thompson TITLE Prod Coordinator

DATE June 11, 1982

APPROVED BY
CONDITIONS OF

(ORIG. SGD.) DAVID R. GLASS

(This space for Federal or State office use)

OCT 15 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

