

NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88410

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Western Reserves Oil Co. /

3. ADDRESS OF OPERATOR
P.O. Box 993 Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FSL & 660' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Surface Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
MAR 18 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE

NM-12438

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bravo Federal

MAY - 6 1982

9. WELL NO.

#4

O. C. D.

ARTESIA, NM

10. FIELD OR WILDCAT NAME

Pecos Slope (Abo)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 30 T-6-S R-25-E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3808.0 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-16-82

Ran & cemented 22 jnts. of 13 3/8" 48# H-40 casing w/ 1000 sx. cement consisting of 300 sx. of Thixset w/ 1/4# Flo-cele per sx., 6# salt per sx., 400 sx. Halliburton-Lite w/ 1/4# Flo-cele per sx. + 6# salt per sx., and 300 sx. class "C" w/ 4% CaCl₂. Had mud returns through out intire job. Circulated 200 sx. cement to surface. Total amount footage of casing on hook, (901.68').

Subsurface Safety Valve: Manu. and Type

Set @ Ft.
ACCEPTED FOR RECORD

18. I hereby certify that the foregoing is true and correct

SIGNED Stephen Knight NRE Agents for
TITLE Western Reserves DATE 3-16-82

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO