Form 9-331 Dec. 1973 UNITED STATESArtesia, NM 88210 DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Budget Bureau No. 42-R1424
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) RECEIVED 1. oil gas well other 2. NAME OF OPERATOR JUN 4 1982 Yates Petroleum Corporation 3. ADDRESS OF OPERATOR O. C. D. 207 South 4th St., Artesia, NM 8874 OFFICE 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE:990 FSL & 660 FEL, Sec. 31-6S-26E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Federal HJ 9. WELL NO. 7 10. FIELD OR WILDCAT NAME 10. FIELD OR WILDCAT NAME 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P, Sec. 31-T6S-R26E 12. COUNTY OR PARISH 13. STATE Chaves 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF X FRACTURE TREAT X SHOOT OR ACIDIZE X PULL OR ALTER CASING X MULTIPLE COMPLETE X CHANGE ZONES X ABANDON* X	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3651.5' GR (NOTE: Report DECONDUCTION OF A CONTROL OF A

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details) SWEEVention of the state of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

.....

: • • •

Spudded a 14-3/4" hole 9:30 AM 5-19-82. Set 70' of 20" conductor pipe. Ran 23 joints of 10-3/4" 40.5# ST&C casing set 910'. 1-Texas Pattern guide shoe at 910'. Flapper float collar at 870'. Cemented w/400 sacks Pacesetter Lite, 2% CaCl₂. Tailed in 300 sacks Class "C" 3% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 5:00 PM 5-20-82. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 11:00 AM 5-21-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

1	ACCEPTED FOR RECORD
Subsurface Safety Valve: Manu. and Type	Ft.
18. Thereby certify that the foregoing is true and correct	JUN 3 1982
SIGNED LON ALUX TITLE Engineering Secty DATE	
(This space for Federal or State office use)	U.S. GEOLOGICAL SURVEY U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO
APPROVED BY TITLE DA	TE ROSWELL

*See Instructions on Reverse Side

الم المحمد المراجعة المحمدة محمد والمحمد والمحمد المراجع المحمد المحمدة المحمد والمحمد والمحمد والمحمد والمحمد محمد مع المحمد المحمد المحمد المحمد المحمد والمحمد المحمد المحمد المحمد المحمد والمحمد والمحمد والمحمد والمحمد و