

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM

Form Approved
Budget Bureau No. 42-R1424

sf/jule

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR ☒
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
990 FNL & 990 FEL, Sec. 19-6S-26E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

- 88210SE NM 2357
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal HJ
9. WELL NO.
8
10. FIELD OR WILDCAT NAME
Picad. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit A, Sec. 19-T6S-R26E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3702' GR

(NOTE: Report results of multiple completion of 82e change on Form 9-330.)

ON A GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole at 9:00 AM 3-17-82. Set 40' of 20" conductor pipe. Ran 24 joints of 10-3/4" 40.5# casing set at 950'. 1-Texas Pattern notched guide shoe at 950'. Insert float at 910'. Cemented w/500 sacks Halliburton Lite 2% CaCl₂. Tailed in w/200 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 10:30 PM 3-19-82. Bumped plug to 700 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out at 4:30 PM 3-20-82. WOC 18 hours. Nipped up and tested to 1100 psi, okay. Reduced hole to 9-7/8" - will drill to 1100' and reduce hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ . . . Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James A. [Signature] TITLE Engineering Secty DATE 3-26-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

MAY 1 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO