	TSU I
m 9–331 ac. 1973	Form Approved. Budget Bureau No. 42–R1424
UNITED STATES LECTRA	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 17031
CISE GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
o not use this form for proposals to drill or to deepen or plug back to a different servoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME APR 3 0 1982
. oil gas the other	BRADEN FEDERAL 9. WELL NO. O. C. D.
	ARTESIA, OFFICE
NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
MESA PETROLEUM CO. /	UNDESIGNATED ABO
B. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701-449	
LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below )	SEC 30, T5S, R24E
at surface: 660' FNL & 660' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	CHAVES NEW MEXICO
AT TOTAL DEPTH:	14. API NO.
5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
FOUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4062'
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
RACTURE TREAT	
HOOT OR ACIDIZE	
	(NOTE: Report results of multiple completion or zone
ULL OR ALTER CASING	1382 011
HANGE ZONES	
	CAL SUBVEY
HANGE ZONES	CAL SURVEY W MEAICO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and
HANGE ZONES       Cill &         BANDON*       U.S.CEDIOG         other)       TD, 4½" CSG & CEMENT       U.S.CEDIOG         17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statistic including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	CAL SURVEY W MEAICO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*
HANGE ZONES BANDON* Other) TD, 4½" CSG & CEMENT 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly static including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled 9 7/8" hole to 1723' with 9.6# mud,	CAL SURVEY W MEALCO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*
HANGE ZONES BANDON* other) TD, 4½" CSG & CEMENT 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji	CAL SURVEY W MEALCO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts $4\frac{1}{2}$ ", 10.5#, K-55 casing set
HANGE ZONES BANDON* other) TD, 4½" CSG & CEMENT 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly station including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji 0 2989' Comented with 400 sx HIW + additive	CAL SURVEY WY MEALCO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts $4\frac{1}{2}$ ", 10.5#, K-55 casing set es and tailed in with 300 sx "C"
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>other) TD, 4½" CSG &amp; CEMENT</li> <li>CONVELL NOT COMPLETED OPERATIONS (Clearly statistic including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji @ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD</li> </ul>	The all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts $4\frac{1}{2}$ ", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>other) TD, 4½" CSG &amp; CEMENT</li> <li>CONVELL NOT COMPLETED OPERATIONS (Clearly statistic including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji @ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD</li> </ul>	The all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts $4\frac{1}{2}$ ", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>Dther) TD, 4½" CSG &amp; CEMENT</li> <li>COWPLETED OPERATIONS (Clearly statistical date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji</li> <li>@ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD of the comparison of the compariso</li></ul>	The second seco
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>other) TD, 4½" CSG &amp; CEMENT</li> <li>CONVELL NOT COMPLETED OPERATIONS (Clearly statistic including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji @ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD</li> </ul>	The second seco
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>Dther) TD, 4½" CSG &amp; CEMENT</li> <li>COWPLETED OPERATIONS (Clearly statistical date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji</li> <li>@ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD of the comparison of the compariso</li></ul>	The all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts $4\frac{1}{2}$ ", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>Other) TD, 41" CSG &amp; CEMENT</li> <li>I.S CFOIGG (OSWALL NET)</li> <li>I.S CFOIGG (OSW</li></ul>	The subset of the state of the
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>Other) TD, 41" CSG &amp; CEMENT</li> <li>I.S CFOIGG (OSWALL NET)</li> <li>I.S CFOIGG (OSW</li></ul>	The subset of the state of the
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>other) TD, 4½" CSG &amp; CEMENT</li> <li>I.S CFOIGGE LOSWALL NET</li> <li>I.S CENTROS</li> &lt;</ul>	The subvey and metal to subsurface locations and directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts 4½", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did 2-82. WOCU estimated to arrive ACCEPTED FOR RECORD ACCEPTED FOR
<ul> <li>HANGE ZONES</li> <li>BANDON*</li> <li>Dther) TD, 4½" CSG &amp; CEMENT</li> <li>COWPLETED OPERATIONS (Clearly statistical date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 ji</li> <li>@ 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD of the comparison of the compariso</li></ul>	The subvey and metal to subsurface locations and directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts 4½", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did 2-82. WOCU estimated to arrive ACCEPTED FOR RECORD ACCEPTED FOR
HANGE ZONES       Image: CSG & CEMENT	The survey and metally and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts 4½", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did 2-82. WOCU estimated to arrive ACCEPTED FOR RECORD ACCEPTED FOR RECORD Ft.
HANGE ZONES       Image: CSG & CEMENT	The survey and metally and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts 4½", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did 2-82. WOCU estimated to arrive ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD Ft.
HANGE ZONES       Image: CSG & CEMENT	ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD NU SWELL AFRILE 9 PARTNERS U.S. GEOLOGICAL SURVEY 0 ORDING SWELL, AFRIL T3, 1982
HANGE ZONES       Image: CSG & CEMENT       Image: CSG & CEMENT         including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine         Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 j: 0 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD in to circulate. Released rig at 12:01 AM 4-1 4-19-82.         XC:       MMS (7), TLS, CEN RCDS, ACCTG, MEC, REM Subsurface Safety Valve: Manu. and Type         18. I hereby,certify that the foregoing is true and correct SIGNED       Mathe Math Mathe Math Mathe Math Mathe Math Mathe Math Math Mathe Mathe Mat	The subvey W MLACO te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* NU BOP's and tested to 600 " and drilled ahead on 4-6-82. ts 4½", 10.5#, K-55 casing set es and tailed in with 300 sx "C" @ 4:30 PM 4-11-82. Cement did 2-82. WOCU estimated to arrive ACCEPTED FOR RECORD ACCEPTED FOR RECORD I, RDSWELLAPHILE, PARTNERS U.S. GEOLOGICAL SURVEY U.S. GEOLOGICAL SURVEY OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO OORDINGSWELL, NEW MEXICO
HANGE ZONES       Image: CSG & CEMENT       Image: CSG & CEMENT         including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine         Drilled 9 7/8" hole to 1723' with 9.6# mud, I psi for 30 mins - 0K. Reduced hole to 7 7/8 Drilled to TD of 4100' on 4-10-82. Ran 96 j: 0 3889'. Cemented with 400 sx HLW + additive + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD in to circulate. Released rig at 12:01 AM 4-1 4-19-82.         XC:       MMS (7), TLS, CEN RCDS, ACCTG, MEC, REM Subsurface Safety Valve: Manu. and Type         18. I hereby,certify that the foregoing is true and correct SIGNED       Mathe Math Mathe Math Mathe Math Mathe Math Mathe Math Math Mathe Mathe Mat	ACCEPTED FOR RECORD ACCEPTED FOR RECORD ACCEPTED FOR RECORD NU SWELL AFRILE 9 PARTNERS U.S. GEOLOGICAL SURVEY 0 ORDING SWELL, AFRIL T3, 1982

•

\*\*\*\*

•

\*See Instructions on Reverse Side

.