

CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501  
MAY 10 1982

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG-252	
7. Unit Agreement Name	
8. Farm or Lease Name Rattlesnake St.	
9. Well No. 1	
10. Field and Pool, or Wildcat Pecos Slope Abo	
12. County Chaves	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator  
T. H. McElvain, Jr.

3. Address of Operator  
P. O. Box 2148, Santa Fe, N.M. 87501

4. Location of Well  
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 5S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3888 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposes or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" at 6:30 P.M. on 4-20-82. Drilled to 970' TD @ 5:00 P.M. on 4-21-82. Ran 24 jts of 8-5/8", 24#, J-55, ST&C 8 Rd, Range 3 casing set at 965' KB. Texas pattern shoe at 965', flapper float at 924'. Cemented with 300 sks of Class C w/ 10#/ sk Gilsonite,, 4% Bentonite, 1/2#/sk cellophane flakes and 2% Ca Cl. Tailed in with 200 sks Class C w/2% Ca Cl. Plug down at 10:15 P.M. 4-21-82. Circulated 150 sks to the pit. WOC 19 hrs. Drilled out plug with 7-7/8" bit at 4:30 P.M. on 4-22-82. Tested to 600# OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED George B. Broome TITLE Geological Engineer DATE 4-30-82

APPROVED BY Mike Walker TITLE OIL AND GAS INSPECTOR DATE MAY 17 1982