

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ **OCT 18 1982**

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FSL & 1980 FWL, Sec. 34-7S-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Lost circulation plug set & production csg. set.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Lost circulation at 1240'. Pulled up and set cement plug as follows:
Spotted 100 sacks Thixolite, 1#/sack Gilsonite, 3#/sack Permacheck, 4#/sack Gilsonite and 3% CaCl₂. Plug set at 1290'. Started pumping cement at 5:37 PM 7-17-82. Shut down at 6:01 PM 7-17-82. WOC 6 hours. Filled hole with fluid. Hole held fluid. Waited 6 hours. Drilled out at 6:00 AM 7-18-82.
TD 4100'. Ran 99 jts of 4-1/2" 9.5# K-55 casing set at 4095'. 1-regular guide shoe at 4095'. Float collar at 4054'. Cemented w/350 sacks 50/50 Poz, .6% CF-9, .3% TF-4 and 3% KCL. Compressive strength of cement - 1250 psi in 12 hrs. PD 1:45 PM 7-23-82. Bumped plug to 1000 psi, released pressure and float held okay. WOC. Ran 1" to 1529' and cemented w/400 sacks Pacesetter Lite. PD 6:00 PM 7-23-82. Circulated 25 sacks to pit.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Engineering Secty DATE 7-28-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY
CONDITIONS OF APPROVAL

OCT 15 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

NM 2351

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal HY

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit N, Sec. 34-T7S-R25E

12. COUNTY OR PARISH

Chaves


13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3554.3' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO